

# EX-PLAST®

BEST QUALITY FINISH



Finder  
[www.jkchemical.in](http://www.jkchemical.in)

Manufactured & Marketed By:-  
**J.K. CHEMICALS**  
151001 (India)  
E-mail: [jkpaints92@gmail.com](mailto:jkpaints92@gmail.com)  
Customer Care No.: +91-869-9570-161

# EX-PLAST®

BEST QUALITY FINISH

Brighten up  
**you house!**

*99 new ideas, 100% colorful*





## Ex-Plast Luxury Gloss Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, Explast All - Latex Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



## Ex-Plast Luxury Glow Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, Explast All - Latex Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



## Ex-Plast Plastic flat Matt Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, Explast All - Latex Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



## Ex-Plast Exterior Cement Primer

Ex-plast Primers can be used as base coat for all types of interior emulsions. Its has been formulated primarily to compliment the performance of all type of emulsions.

- Fill surface imperfections such as hairline cracks for a uniform painting surface.
- Adhere to and cover surfaces thoroughly.
- Seal off stains that may otherwise show.
- Apply ColorCoat primers on wide range of painted or unpainted surfaces.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	150-200 SQ ft/ltr./coat on a well prepared surface
SHADE	White
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

### FEATURES

- Excellent adhesion.
- Excellent hiding.
- Great flow & leveling.
- Quick drying.
- Greater Coverage.
- Low Odour.



## Ex-Plast Wall Primer Interior

With the sole Purpose of providing unsurpassed protections and beautification, Explast All - Latex Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



## Ex-Plast Waterproof Wall Putty

Ex-Plast Waterproof Wallputty is a white cement based products with re-dispersible polymers and functional additives for application on exterior & interior rough plasters to give a smooth finish.

METHOD OF APPLICATION	Putty Knife, Trowal
DILUTION	Water (if desired)
DRYING TIME	1-2 Hrs. (30°C & relative humidity)
RE-COAT TIME	4-6 hours
COVERAGE	20sq.ft./ Kg. (at 200 microns thickness)
SHADE	White
PACKAGING	20Kg. 40Kg.

### FEATURES

- Applicable on both new or old wall surfaces.
- Gives a smooth & bright finish.
- Controlled water vapour permeability.
- Resists the growth of algae and fungi on wall.
- Good Intercoat adhesion to Emulsion Paints.
- Reduction in airborne dust



## Ex-Plast Luxury Quality Wall Putty

Ex-Plast Luxury Wallputty is a white cement based products with re-dispersible polymers and functional additives for application on exterior & interior rough plasters to give a smooth finish.

METHOD OF APPLICATION	Putty Knife, Trowal
DILUTION	Water (if desired)
DRYING TIME	1-2 Hrs. (30°C & relative humidity)
RE-COAT TIME	4-6 hours
COVERAGE	20sq.ft./ Kg. (at 200 microns thickness)
SHADE	White
PACKAGING	20Kg. 40Kg.

### FEATURES

- Applicable on both new or old wall surfaces.
- Gives a smooth & bright finish.
- Controlled water vapour permeability.
- Resists the growth of algae and fungi on wall.
- Reduction in airborne dust



## Super Birlacem Plus Cement Paint

Cement Paint can be used as base coat for all types of interior emulsions. Its has been formulated primarily to compliment the performance of all type of emulsions.

Professional Cement Paint has been manufactured for above grade masonry surfaces where a high performance primer is needed. It is efflorescence and alkali resistant and will increase and reinforce the performance of the paints. It can be used on properly prepared concrete, concrete block, brick and stucco. Interior primer is also designed for use on interior wood and plywood siding and trim. It can be used for priming new or previously painted walls, ceilings & wooden surfaces.

METHOD OF APPLICATION	Brush, Roller or Spray
DILUTION	Water Ratio 400-500ml. Per Ltr.
DRYING TIME	Surface dry 60-90 minutes/Hard dry-24-48 Hrs.
RE-COAT TIME	At an interval of 2-4 hours
COATING SYSTEM	2-3 Coats as required
SHADE	White
PACKAGING	40kg Bag. / 20Kg. Bucket