

ULTRA PLUS

AN ISO 9001:2015 CERTIFIED CO.

ULTRA PLUS



For Beautiful Home

HOUSING COLOUR BOOK

 **USA**
TECHNICAL SUPPORT

ANIKA ENTERPRISES
Customer Care No.: +91-869-9570-161

MADE IN INDIA



UltraPlus Semi Gloss Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, UltraPlus Semi Gloss All - Plastic Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



UltraGlow Silk Touch Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, UltraGlow Silk Touch All - Plastic Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



Ultra Plus Exterior Cement Primer

- Fill surface imperfections such as hairline cracks for a uniform painting surface.
- Adhere to and cover surfaces thoroughly.
- Seal off stains that may otherwise show.
- Apply ColorCoat primers on wide range of painted or unpainted surfaces.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	150-200 SQ ft/ltr./coat on a well prepared surface
SHADE	White
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

FEATURES

- Excellent adhesion.
- Excellent hiding.
- Great flow & leveling.
- Quick drying.
- Greater Coverage.
- Low Odour.

UltraPlus Acrylic Washable Distemper

With the sole Purpose of providing unsurpassed protections and beautification, UltraPlus Premium All - Acrylic Washable Distemper Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Kg. 10Kg. 5Kg.

- ✓ Premium Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



UltraPlus Nano Shield Plastic Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, Nano Shield All - Plastic Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



UltraPlus Wall Sealer Primer+Emulsion

With the sole Purpose of providing unsurpassed protections and beautification, UltraPlus Wall Sealer All - Primer + Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft/ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

- ✓ Luxury Finish
- ✓ Low Odor, Low Voc
- ✓ Weather Protection



Ultra Plus Wall Putty

Ultra Plus Premium Wallputty is a white cement based products with re-dispersible polymers and functional additives for application on exterior & interior rough plasters to give a smooth finish.

METHOD OF APPLICATION	Putty Knife, Trowel
DILUTION	Water (if desired)
DRYING TIME	1-2 Hrs. (30°C & relative humidity)
RE-COAT TIME	4-6 hours
COVERAGE	20sq.ft./ Kg. (at 200 microns thickness)
SHADE	White
PACKAGING	20Kg. 40Kg.

FEATURES

- Applicable on both new or old wall surfaces.
- Gives a smooth & bright finish.
- Controlled water vapour permeability.
- Resists the growth of algae and fungi on wall.
- Good Intercoat adhesion to Emulsion Paints.
- Reduction in airborne dust

Super Camel Plus Cement Paint

Cement Paint can be used as base coat for all types of interior emulsions. Its has been formulated primarily to compliment the performance of all type of emulsions.

Professional Cement Paint has been manufactured for above grade masonry surfaces where a high performance primer is needed. It is efflorescence and alkali resistant and will increase and reinforce the performance of the paints. It can be used on properly prepared concrete, concrete block, brick and stucco. Interior primer is also designed for use on interior wood and plywood siding and trim. It can be used for priming new or previously painted walls, ceilings & wooden surfaces.

METHOD OF APPLICATION	Brush, Roller or Spray
DILUTION	Water Ratio 400-500ml. Per Ltr.
DRYING TIME	Surface dry 60-90 minutes/Hard dry-24-48 Hrs.
RE-COAT TIME	At an interval of 2-4 hours
COATING SYSTEM	2-3 Coats as required
SHADE	White
PACKAGING	40kg Bag. / 20Kg. Bucket

FEATURES

- Excellent adhesion.
- Excellent hiding.
- Great flow & leveling.
- Quick drying.
- Greater Coverage.
- Low Odour.

