

JKC paints

For Beautiful Home



AN ISO 9001:2015 CERTIFIED CO.

Paints that
do more



Finder
www.jkchemical.in

J.K. CHEMICALS
Customer Care No.: +91-869-9570-161
E-mail: jkcpaint92@gmail.com





HI-SHEEN EMULSION

With the sole Purpose of providing unsurpassed protections and beautification, JKC PAINTS's All - Hi-Sheen Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft./ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.



GLOW EMULSION

With the sole Purpose of providing unsurpassed protections and beautification, JKC PAINTS's All - Glow Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft./ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.



LUXURY EMULSION

With the sole Purpose of providing unsurpassed protections and beautification, JKC PAINTS's All - Luxury Emulsion Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft./ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.



PAINT & PRIMER

With the sole Purpose of providing unsurpassed protections and beautification, JKC PAINTS's All - Paint & Primer Provides the best performance for you home.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	300-400 SQ ft./ltr./coat on a well prepared surface
SHADE	White & bases
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.



INTERIOR & EXTERIOR PRIMER

JKC PAINTS Primer our Most Advanced Paint & Primer in One Guaranteed One Coat Hide in over 1000 colors* Superior Durability & Stain Resistance Scrubbable easy Clean Finish Coverage per Gallon: UP TO 400sq.ft.

METHOD OF APPLICATION	Brush, roller or spray
DILUTION	Water
DRYING TIME	Surface dry 60 minutes/Hard dry-14 days
RECOAT TIME	At an interval of 2-4 hours
COVERAGE	130-150 SQ ft./ltr./coat on a well prepared surface
SHADE	White
PACKAGING	20Ltr. 10Ltr. 4Ltr. 1Ltr.

FEATURES

- Excellent adhesion.
- Excellent hiding.
- Great flow & leveling.
- Quick drying.
- Greater Coverage.
- Low Odour.

DAMPCARE PUTTY

JKC Water Proof Wallputty is a white cement based products with water resistant polymers and functional additives for application on exterior & interior rough plasters to give a smooth finish.

METHOD OF APPLICATION	Putty Knife, Trowel
DILUTION	Water (if desired)
DRYING TIME	1-2 Hrs. (30°C & relative humidity)
RE-COAT TIME	4-6 hours
COVERAGE	30sq.ft./ Kg. (at 200 microns thickness)
SHADE	White
PACKAGING	20Kg.

- Unique Velvet Finish
- Stain Resistant
- Excellent Hiding
- Washable & Scrubbable



POLYMER PUTTY

JKC Premium Wallputty is a white cement based products with re-dispersible polymers and functional additives for application on exterior & interior rough plasters to give a smooth finish.

METHOD OF APPLICATION	Putty Knife, Trowel
DILUTION	Water (if desired)
DRYING TIME	1-2 Hrs. (30°C & relative humidity)
RE-COAT TIME	4-6 hours
COVERAGE	20sq.ft./ Kg. (at 200 microns thickness)
SHADE	White
PACKAGING	20Kg. 40Kg.

FEATURES

- Applicable on both new or old wall surfaces.
- Gives a smooth & bright finish.
- Controlled water vapour permeability.
- Resists the growth of algae and fungi on wall.
- Good Intercoat adhesion to Emulsion Paints.
- Reduction in airborne dust

INTRODUCING: SUPER JAYKAY CEMENT PAINT

Cement Paint can be used as base coat for all types of interior emulsions. Its has been formulated primarily to compliment the performance of all type of emulsions.

Professional Cement Paint has been manufactured for above grade masonry surfaces where a high performance primer is needed. It is efflorescence and alkali resistant and will increase and reinforce the performance of the paints. It can be used on properly prepared concrete, concrete block, brick and stucco. Interior primer is also designed for use on interior wood and plywood siding and trim. It can be used for priming new or previously painted walls, ceilings & wooden surfaces.

METHOD OF APPLICATION	Brush, Roller or Spray
DILUTION	Water Ratio 400-500ml. Per Ltr.
DRYING TIME	Surface dry 60-90 minutes/Hard dry-24-48 Hrs.
RE-COAT TIME	At an interval of 2-4 hours
COATING SYSTEM	2-3 Coats as required
SHADE	White
PACKAGING	40kg Bag. / 20Kg. Bucket

